

HARTER, SECREST & EMERY LLP
ATTORNEYS AT LAW

B2 Sub D' 7 4. (Once Amended) The method of Claim 1, wherein sensing the corresponding resulting change includes sensing at an upstream location to the introduced volume and a downstream location to the introduced volume.

5. The method of Claim 1, wherein sensing the corresponding resulting change includes employing a sensor located at one of in the conduit, on the conduit or spaced from an exterior of the conduit.

B3 Sub D' 7 6. (Once Amended) The method of Claim 1, wherein introducing the discrete known volume over a known time includes introducing the discrete known volume over a known time through a catheter in the conduit.

7. The method of Claim 1, further comprising sensing the corresponding resulting change in one of a liquid characteristic and a flow characteristic.

8. The method of Claim 1, wherein sensing a corresponding resulting change includes sensing a corresponding resulting change proportional to the flow in the conduit.

9. The method of Claim 1, wherein sensing a corresponding resulting change includes sensing one of a velocity, pressure and flow rate of the flow in the conduit.

10. The method of Claim 1, wherein sensing a corresponding resulting change includes sensing a dilution indicator.

Sub D' 7 B4 11. (Once Amended) A method for determining an initial flow rate in a conduit, comprising:

- (a) locating a catheter in the conduit;
- (b) introducing a known flow rate to the initial flow rate through the catheter; and
- (c) determining the initial flow rate in response to the introduced known flow rate and a resulting change in the initial flow rate.

12. (Once Amended) The method of Claim 11, wherein introducing a known flow rate includes introducing a discrete volume change.

13. (Once Amended) The method of Claim 11, wherein introducing a known flow rate includes injecting or withdrawing a discrete volume from the conduit.

HARTER, SECREST & EMERY LLP
ATTORNEYS AT LAW

14. The method of Claim 11, further comprising employing one of a flow characteristic sensor and a liquid characteristic sensor.

B5 Jul 17 15. (Once Amended) The method of Claim 11, wherein sensing the corresponding resulting change includes sensing at an upstream location to the introduced known flow rate and a downstream location to the introduced known flow rate.

16. The method of Claim 11, wherein sensing a corresponding resulting change includes sensing with a sensor located at one of in the conduit, on the conduit or spaced from an exterior of the conduit.

B6 Jul 17 17. (Once Amended) The method of Claim 11, further comprising sensing a resulting change after introducing the known flow rate.

18. (Once Amended) The method of Claim 17, wherein sensing the resulting change includes sensing a change corresponding to the introduced known flow rate in one of a liquid characteristic and a flow characteristic.

19. The method of Claim 17, further comprising sensing a resulting change as proportional to the flow in the conduit.

B7 Jul 17 20. (Once Amended) A method for determining an initial flow rate in a conduit, comprising:

- (a) introducing a discrete known volume over a known time to the initial flow in the conduit to produce a resulting change in the initial flow; and
- (b) determining the initial flow rate in response to the introduced discrete known volume, the known time and the resulting change.

21. The method of Claim 20, further comprising employing a sensor to sense the resulting change in the flow.

B8 Jul 17 22. (Once Amended) An apparatus for determining an initial flow rate in a conduit, comprising:

- (a) means for introducing a discrete known volume over a known time to the initial flow;

HARTER, SECREST & EMERY LLP
ATTORNEYS AT LAW

Completed
b8
p. 17
(b) a sensor for measuring a corresponding change resulting from the introduced discrete known volume over the known time; and

(c) a controller connected to the sensor, the controller configured to determine the initial flow rate in a response to the known volume, the known time and the corresponding change.

23. The apparatus of Claim 22, further comprising a catheter having an introduction port.

24. The apparatus of Claim 23, wherein the sensor is connected to the catheter.

b9
p. 17
25. (Once Amended) An apparatus for determining an initial flow rate in a conduit, comprising:

(a) a known flow rate introducer selected to effect a discrete known flow rate to produce a resulting change in the initial flow in the conduit;

(b) a sensor for measuring the resulting change; and

(c) a controller connected to the sensor, the controller configured to determine the initial flow rate in a response to the known flow rate and the resulting change measured by the sensor.

26. (Once Amended) A method for determining an initial blood flow rate in a conduit, comprising:

(a) introducing a known flow rate of an indicator into the conduit to create a discrete volume change in the initial flow and a liquid characteristic change in the conduit;

(b) optically sensing the liquid characteristic change in the conduit with a sensor located external to the conduit; and

(c) determining the initial blood flow rate in the conduit in response to the introduced known flow rate of indicator and the sensed liquid characteristic change.

27. (Once Amended) The method of Claim 26, wherein introducing the known flow rate of the indicator includes introducing a change in blood hematocrit in the conduit.

28. (Once Amended) The method of Claim 26, wherein introducing the known flow rate of the indicator includes introducing a solution including at least one of saline and glucose into the conduit.

HARTER, SECREST & EMERY LLP
ATTORNEYS AT LAW

29. The method of Claim 28 further comprising introducing an isotonic solution into the conduit.

30. The method of Claim 26, wherein optically sensing the liquid characteristic change includes obtaining a value proportional to the liquid characteristic change.

31. (Once Amended) The method of Claim 26, wherein introducing the volume of the indicator into the conduit includes introducing the known flow rate of indicator upstream of an area sensed by the optical sensor.

32. The method of Claim 26, wherein the liquid characteristic is blood hematocrit.

33. The method of Claim 26, wherein optically sensing the liquid characteristic change includes obtaining a value proportional to blood hematocrit in the conduit.

34. (New) The method of Claim 1, further comprising measuring to identify one of the known volume and the known time.

35. (New) The method of Claim 11, further comprising determining the known flow rate by measuring.

36. (New) The method of Claim 20, wherein one of the known volume and the known time is determined by measuring.

37. (New) A method for determining an initial blood flow rate in a conduit, comprising:

(a) determining the initial blood flow rate Q_i corresponding to at least one of the following and an analogous relationships:

$$Q = \frac{Q_i}{\left(\frac{\Delta Q_d}{Q_d} - \frac{\Delta Q_u}{Q_u} \right)}; Q = \frac{Q_i}{(C_{bd} - C_{bu})}; Q = \frac{Q_i}{\left(\frac{\Delta V_d}{V_d} - \frac{\Delta V_u}{V_u} \right)}; Q = \frac{Q_i}{\left(\frac{\Delta hu}{h_{ui}} - \frac{\Delta hd}{h_{di}} \right)};$$

$$Q = \frac{Q_i}{\left(\frac{\Delta P_d}{P_d - P_{ven}} - \frac{\Delta P_u}{P_u - P_{art}} \right)}$$

HARTER, SECREST & EMERY LLP
ATTORNEYS AT LAW

where Q_i is the introduced volume during the introduced time;

$$\Delta Q_d = Q_{di} - Q_d;$$

$$\Delta Q_u = Q_{ui} - Q_u;$$

Q_d is the flow rate downstream of an introduction point of Q_i ;

Q_u is the flow rate upstream of an introduction point of Q_i ;

C_{bd} is the relative change in a flow corresponding parameter from an upstream volume injection;

C_{bu} is the relative change in a flow corresponding parameter from a downstream volume injection;

ΔV_u is a change corresponding to an upstream blood velocity;

ΔV_d is a change corresponding to a downstream blood velocity;

V_u is an upstream blood velocity;

V_d is a downstream blood velocity;

h_u is a concentration of indicator measured at an upstream sensor;

h_d is a concentration of indicator measured at a downstream sensor;

$$\Delta h_u = h_{ui} - h_u; \text{ and}$$

$$\Delta h_d = h_{di} - h_d.$$

38. (New) A method for determining an initial blood flow rate in a conduit, comprising:

(a) determining the initial blood flow rate Q_i corresponding to an introduced flow rate to the initial flow rate.